

	PART NO.	NUMBER OF OUTLETS	CONNECTION TYPE	"A"	"В"	"c"
	QJ363F-1000-1-NYB QJ364F-1000-1-NYB QJ365F-1000-1-NYB	4 5 6	1" SINGLE HOSE BARB	2.18" (55 mm)	3.20" (81 mm)	3.66" (93 mm)
	QJ363F-1000-2-NYB QJ364F-1000-2-NYB QJ365F-1000-2-NYB	4 5 6	1" DOUBLE HOSE BARB	3.38" (86 mm)	3.20" (81 mm)	3.66" (93 mm)

Note: "A", "B", & "C" dimensions are approximate.

FEATURES:

- QUICK HAND INDEXING WITH CHOICE OF THREE, FOUR, OR FIVE OUTLET TURRET. SINGLE FERTILIZER OUTLET ALSO STANDARD.
- ALLOWS FOR RAPID CHANGE OF SPRAY TIPS WITH USE OF QUICK TEEJET CAPS.
- POSITIVE SHUT-OFF BETWEEN EACH SPRAY POSITION.
- MADE OF CORROSION RESISTANT MATERIALS.
- STANDARD O-RINGS AND DIAPHRAGM MADE OF EPDM, TEFLON FILLED EPDM, AND BUNA-N.
- OPTIONAL O-RINGS AND DIAPHRAGM MADE OF VITON AND TEFLON FILLED VITON.
- STANDARD OPENING PRESSURE 10 PSI (0.7 bar)
- MAXIMUM OPERATING PRESSURE 300 PSI (20 bar).
- FLOW RATES: 2.25 GPM (8.5 I/min) WITH 5 PSI DROP THROUGH TURRET,
 3.4 GPM (12.9 I/min) WITH 5 PSI DROP THROUGH FERTILIZER OUTLET.
- HEX SOCKET IN CENTER OF UPPER CLAMP PERMITS ATTACHMENT OF BODY TO FLAT SURFACE USING CUSTOMER SUPPLIED FASTENER.
- CLAMP ASSEMBLY WILL FIT INSIDE COMMON CHANNELS USED FOR SPRAY BOOMS.
- AVAILABLE WITH 1" SINGLE OR DOUBLE HOSE BARB CONNECTION.
- IF TURRET BECOMES DIFFICULT TO TURN REMOVE E-CLIP, SLIDE TURRET OFF BODY, AND LUBRICATE O-RINGS AND SEAL WITH A SILICONE BASED LUBRICANT.
- FOR TIP RECOMMENDATIONS AND APPLICATION RATES SEE DATA SHEETS QJ360F (SHEETS 1 AND 2), QJ360FM (SHEETS 1 AND 2), & QJ360F-2.

HOW TO ORDER:

QJ365F-1000-1-NYB - 1" SINGLE HOSE BARB NOZZLE BODY ASSEMBLY

QJ365F-1000-1-NYB-VI - 1" SINGLE HOSE BARB NOZZLE BODY ASSEMBLY W/ VITON DIAPHRAGM AND O-RINGS

QJ365F-1000-2-NYB - 1" DOUBLE HOSE BARB NOZZLE BODY ASSEMBLY

QJ365F-1000-2-NYB-VI - 1" DOUBLE HOSE BARB NOZZLE BODY ASSEMBLY W/ VITON DIAPHRAGM AND O-RINGS

DESCRIPTION:

QJ360F DIAPHRAGM CHECK VALVE QUICK TEEJET® HINGED NOZZLE BODY ASSEMBLY



© Spraying Systems Co.
