



**FEATURES:**

- DESIGNED FOR USE WITH QUICK TEEJET® VARI-SPACING CLAMPS - SEE D.S. 21386-4.
- USED WITH QUICK TEEJET® CAPS
- HOSE SHANK AVAILABLE AS SINGLE, OR DOUBLE IN 3/8", 1/2", AND 3/4" SIZES.
- MADE OF CORROSION RESISTANT MATERIALS.
- DRIP FREE POSITIVE SHUT-OFF.
- LOW PROFILE DESIGN ALLOWS MAXIMUM PROTECTION AGAINST DAMAGE.
- MAXIMUM OPERATING PRESSURE (NYLON) 300 PSI (20 bar)
- \* ● MAXIMUM OPERATING PRESSURE (PP) 150 PSI (10 bar)

STYLE	BODY No.	"A" DIM. (APPROX.)	"B" DIM. (APPROX.)	"C" DIM. (APPROX.)
SINGLE	22251-311-375-NYB*	2" (51 mm)	2 1/2" (63 mm)	1 7/16" (36 mm)
	22251-311-500-NYB*	2" (51 mm)	2 1/2" (63 mm)	1 7/16" (36 mm)
	22251-311-750-NYB*	2 1/3" (59 mm)	2 1/2" (63 mm)	1 7/16" (36 mm)
DOUBLE	22252-312-375-NYB*	3 1/8" (79 mm)	2 1/2" (63 mm)	1 7/16" (36 mm)
	22252-312-500-NYB*	3 1/8" (79 mm)	2 1/2" (63 mm)	1 7/16" (36 mm)
	22252-312-750-NYB*	3 3/4" (95 mm)	2 1/2" (63 mm)	1 7/16" (36 mm)

\* -PP FOR POLYPROPYLENE MATERIAL

**DESCRIPTION:**  
**QJ300 SERIES HOSE SHANK  
 DIAPHRAGM CHECK VALVES**



**Spraying Systems Co.®**  
 Spray Nozzles and Accessories  
 P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 3  
 Ref.

Data Sheet No.  
**21386-3**  
 SHEET OF