

TEEJET SPRAY DEMONSTRATION TANKS DURABLE, COMPACT, PORTABLE



The TeeJet Spray Demonstration Tank is a rugged, self-contained unit designed to demonstrate a wide range of agricultural spray tips. This tank is ideal for use at tradeshows, training events, field days or in the retail showroom. The compact design and storage case allow for easy transport and quick setup by a single person. The standard case includes wheels and telescoping handle for easy mobility.

Features:

- Choice of tank material:
 - 304 Stainless steel, continuously welded tank construction for exceptional strength and durability
 - Polyethylene, molded tank construction for light weight and easy transport
- Stainless steel boom fitted with two or three multiple outlet nozzle bodies can hold a variety of different spray tips
- Top or face mounted dual scale pressure gauge for easy readout
- Pressure relief valve mounted next to gauge for pressure adjustment
- Tank mounted, diaphragm pump provides good performance in a compact size
- Choice of 110 or 220V AC electrical service
- Push to connect plumbing connections for easy servicing
- Durable, remote controlled LED lighting illuminates spray pattern for better viewing
- Inline strainer to prevent plugging
- Drain port for fast, complete draining



TEEJET SPRAY DEMONSTRATION TANKS

Specifications:

PART #	TANK CONSTRUCTION	WATER CAPACITY	VOLTAGE	PRESSURE*	BOOM	WEIGHT
LI-TJ180-110-DX	304SS	3 gal (11.4 L)	110-VAC 50/60 Hz	120 psi (8.3 bar) w/ single 03 tip	1/2" 304SS pipe with 3 QJ375	87 lbs. (40 kg) with case
LI-TJ180-220-DX	304SS	3 gal (11.4 L)	220-VAC 50/60 Hz	120 psi (8.3 bar) w/ single 03 tip	1/2" 304SS pipe with 3 QJ375	87 lbs (40 kg) with case
LI-TJ200-110-DX	Polyethylene	1 gal (3.8 L)	110-VAC 50/60 Hz	120 psi (8.3 bar) w/ single 03 tip	1/2" 304SS pipe with 2 QJ375	50 lbs. (23 kg) with case
LI-TJ200-220-DX	Polyethylene	1 gal (3.8 L)	220-VAC 50/60 Hz	120 psi (8.3 bar) w/ single 03 tip	1/2" 304SS pipe with 2 QJ375	50 lbs. (23 kg) with case

- Spray tanks include deluxe case (Black ABS plastic construction, buckle & strap closure, with foam liner, dual wheels & telescoping pull handle)

- Spray tank lighting is remote control operated, dimmable and strobing. 100-240V AC, 50/60 Hz.

* Higher Performance pump available upon request

How to order:

Part Number	Description
LI-TJ180-110-DX	Stainless Steel Spray tank with deluxe case and 110-VAC pump
LI-TJ180-220-DX	Stainless Steel Spray tank with deluxe case and 220-VAC pump
LI-TJ200-110-DX	Polyethylene Spray tank with deluxe case and 110-VAC pump
LI-TJ200-220-DX	Polyethylene Spray tank with deluxe case and 220-VAC pump

Dimensions:

